

SYS 1357

Plug-in

15 ~ 24W

Country of Origin : China
Operating Temperature : 0 ~ 40°C
Dimension : 92.6 x 45.5 x 36.2 mm
Approvals / Marks : TÜV/GS, BSMI, SAA/Victoria,
CCC, UL, PSE, S-mark, T-mark,
CE, VCCI, C-tick, FCC



Features:

Wall-mount Adapter with Exchangeable Plug

Wide input voltage range 90~264 VAC

Output voltage available 12 VDC (others under developing)

Output connector: standard: 2.1 x 5.5 x 11mm or customer requirement

1 year warranty

Specification:

	MODEL	Voltage	Current	Tolerance	Ripple & Noise	Max. Power
OUTPUT	SYS1357-1505	5 VDC	3.00 A	5%	100mV	15W
	SYS1357-1809	9 VDC	2.00 A	5%	100mV	18W
	SYS1357-2412	12 VDC	2.00 A	5%	120mV	24W
	SYS1357-2415	15 VDC	1.60 A	5%	150mV	24W
	SYS1357-2418	18 VDC	1.33 A	5%	180mV	24W
	SYS1357-2424	24 VDC	1.00 A	5%	240mV	24W
		Efficiency (typ)	78.7% @ full load			
INPUT	Voltage	90 ~ 264VAC				
	Frequency	47 ~ 63 Hz				
	Current	1A @ 90VAC input and DC output full load				
	Inrush Current	40A @ 115VAC, 60A @ 230VAC low line input and DC output full load				
	Leakage Current	< 0.25mA max.				
PROTECTION	Over Current	> 3.3 ~ 5.5A				
	Short Circuit	Is defined as any output impedance of less than 0.1ohms				
OTHERS	Standby Power	0.3W max.				
	Cooling	Free air convection				
	Withstand Voltage	I/P-O/P: 3000VAC				
Environment	Temperature	Operating: 0 ~ 40°C / Storage: -20 ~ 85°C				
	Humidity	Operating: 8% ~ 90% RH (non condensing) / Storage: 5% ~ 95% RH (non condensing)				
Connection	Input	Plugs: EU, UK, US, AUS, China, Japan (exchangeable)				
	Output	Plug: standard: 2.1x5.5x11mm, center '+' or customer requirement // Cable: 180cm				
M.T.B.F.	35 K hours					
SAFETY	Approved: UL 60950-1, 1 st Edition, 2006-07 (Information Technology Equipment – Safety – Part 1: General Requirements) CSA C22.2 No. 60950-1-03, 1 st Edition, 2006-07 (Information Technology Equipment – Safety – Part 1: General Requirements)					
EMC	Meet EN55022 class B, FCC part 15 Sub part B class B					
WEIGHT	N.W.: 0.155 kg					